



Never compromise on quality!

# SILICONE RELEASE SPRAY

**Aerosol Lubricating Oil** 



## INDUSTRIAL GLUES & ADHESIVES RANGE

# **Description:**

A silicone lubricating oil in an aerosol can.

## Uses

Bond It SILICONE RELEASE SPRAY can be used for conveyors in the food and drink industry where a food safe non emulsifying lubricant is required. The moulding industry to improve productivity and ease of release. Textile industry where a clean non staining lubricant is required. Automotive to prevent door gaskets sticking and interior trim squeaks. This product will not attack painted surfaces or plastics.

#### **Application**

Spray in short bursts on to the surfaces that require lubrication, wipe away excess with a soft cloth.

For mould release applications remove any material from the mould, spray uniformly paying particular attention to corners and areas of fine detail. Ensure all surfaces have received a coating, the silicone can be gently spread using a soft non woven cloth. Best results will always be achieved from moulds with smooth unpitted finishes.

#### **Limitations**

Do not use on surfaces to be painted as silicone may induce surface irregularities in the paint. For polystyrene, first spray the release onto a cloth and apply by hand to protect the polystyrene from the propellant.

#### **Container Size**

500ml aerosol tin.

#### **Shelf Life**

12 months from date of manufacture, when stored in original, unopened canister. See neck of can for batch reference.

#### **Storage Conditions**

Store below 30°C in a dry, well ventilated place away from sources of heat, ignition and direct sunlight. No smoking. Observe the

label precautions. **SILICONE RELEASE SPRAY** must be stored in accordance with the flammable liquid storage regulations.

## **Disposal of Containers**

Do not leave empty containers where residue could be harmful to children, animals or the environment. Replace lids and remove any containers to a central disposal point in accordance with local regulations. Do not pierce canister.

Spilt material should be mopped up immediately with an absorbent cloth and a suitable solvent cleaner.

#### **Health & Safety**

Highly flammable. Please refer to separate material safety data sheet for full handling, use and storage instructions. Keep out of reach of children. It is the users responsibility to determine suitability for use. If in doubt contact our Technical Department for advice.

Note: this information is for general guidance only, since site conditions and labour are beyond our control. It is recommended that users make their own tests to determine suitability.

| Specification Summary |                  |
|-----------------------|------------------|
| Appearance            | Colourless oil   |
| Flammability          | Highly flammable |
| Flash Point           | -40°C            |
| Boiling Point         | 35℃              |
| рН                    | N/A              |
| Solubility in Water   | Insoluble        |
| UFI                   |                  |

## **Product Details:**

| Code:    | BISR500       |
|----------|---------------|
|          |               |
| Size:    | 500ml         |
| Barcode: | 5060021361370 |



Part of the Bond It Glues & Adhesives Range



Head Office: Unit G16 River Bank Way, Lowfields Business Park, Elland, West Yorkshire HX5 9DN.

Telephone: +44 (0)1422 315300 Fax +44 (0)1422 315310 Email: salesuk@bonditgroup.com Website: www.bonditgroup.com



expressed or implied, of the fitness or suitability of the products for a particular purpose.

The data presented in this leaflet are in accordance with the present state of our knowledge, but do not absolve the user from carefully checking all supplies immediately on receipt. We reserve the right to alter product constants within the scope of technical progress or new developments. The recommendations made in this leaflet should be checked by preliminary trials because of conditions during processing over which we have no control, especially where other companies raw materials are also being used. The recommendations do not absolve the user from the obligation of investigating the possibility of infringement of third parties rights and, if necessary clarifying the position. Recommendations for use do not constitute a warranty, either

V2 20/05/20 Supercedes: V1 30/09/02



