



Never compromise on quality!



BUILDERS COMPLETE RANGE

POWDERED CEMENT DYE

Cement Colourant

Description

A easily dispersed premium grade permanent colourant for mortars and renderings. Conforms to EN 12878

Uses

For permanently colouring cements, mortars, concretes and renderings. Suitable for use in conjunction with other admixtures, e.g. Bond It LIQUID MORTAR PLASTICISER, INTEGRAL WATERPROOFER, FROSTPROOFER AND HARDENER and SBR ADMIXTURE.

Application

Pre-mix Bond It **POWDERED CEMENT DYE** into the dry sand/cement mixture either by hand or machine, before adding the gauging water. To ensure you are able to match the colour, always weigh the cement dye and the cement, do not gauge by volume. For lighter shades reduce the amount of dye added.

Limitations

Do not exceed 5Kgs of dye per 50Kgs of cement as the quality of the mortar could be compromised.

Storage Conditions

Store in cool, dry conditions in a sealed container.

Shelf Life

Up to 5 years when stored according to manufacturers instructions.

Coverage

Maximum 5Kgs dye to 2 x 25Kgs cement.

Disposal of Containers

Do not leave empty containers where residue could be harmful to children, animals or the

environment. Replace lids and remove any containers to a central disposal point in accordance with local regulations.

Health & Safety


- ◆ Flammability - non-flammable.
- ◆ Low hazardous product - safe in normal use.
- ◆ Avoid eye contact, wear eye and face protection.
- ◆ Avoid prolonged contact with skin. Wear protective clothing and gloves.
- ◆ Do not ingest.
- ◆ Thoroughly wash hands with soap and water after use.
- ◆ Keep out of reach of children.
- ◆ Some people are more sensitive to chemical products than others. If irritation occurs discontinue use.
- ◆ See separate material safety data sheet for full handling, use and storage.

Specification Summary

Flammability	Non Flammable
pH	N/A
Solubility in water:	Insoluble
Composition	Mixture based on inorganic metallic oxides

Container Sizes

Colour:	Black	Brown
Code:	BDH060BL	BDH060BR
Size:	1Kg	1Kg
Barcode:	5060021361233	5060021361240
Colour:	Red	Yellow
Code:	BDH060R	BDH060Y
Size:	1Kg	1Kg
Barcode:	5060021361257	5060021361264

 0120	
BOND IT G16 River Bank Way, Lowfields Business Park, Elland, West Yorkshire. HX5 9DN 13	
GB13/89081 EN12878 Intended to be used in concrete, mortar and grout applications	
Setting Time Compressive Strength Composition of Pigments Water Soluble Substances Water Soluble Chlorides Total Chlorine Loss of Ignition Dangerous Substances	Pass Category A Pass Cat A Cat A Category A Buff: 14%; Brick Red:1%; Russet Brown: 12%; Black: 24%; * Dark Brown: 3%; * Tile Red: 1% None

* Only available in Ireland

The data presented in this leaflet are in accordance with the present state of our knowledge, but do not absolve the user from carefully checking all supplies immediately on receipt. We reserve the right to alter product constants within the scope of technical progress or new developments. The recommendations made in this leaflet should be checked by preliminary trials because of conditions during processing over which we have no control, especially where other companies raw materials are also being used. The recommendations do not absolve the user from the obligation of investigating the possibility of infringement of third parties rights and, if necessary clarifying the position. Recommendations for use do not constitute a warranty, either express or implied, of the fitness or suitability of the products for a particular purpose.



Certificate Number: 6152
ISO 9001
ISO 14001



BOND IT
 Unit G16 River Bank Way, Lowfields Business Park,
 Elland, West Yorkshire HX5 9DN.
 Telephone: +44 (0)1422 315300 Fax +44 (0)1422 315310
 Email: sales@bond-it.co.uk Website: www.bond-it.co.uk



V2 3/12/12

