



Never compromise on quality!

Published: June 2003

ANTI-CLIMB PAINT

Non-Drying Deterrant Paint

Description

A non-oxidising specialist paint, developed to deter and prevent unwanted intruders from entering premises as it remains soft and slippery. Contains special identifying agent.

Uses

Bond It **ANTI-CLIMB PAINT** is formulated to remain soft and slippery making it virtually impossible to climb or scale coated surfaces.

It is ideal for use on metal and wooden fences, brick walls, sills, gutters, fall pipes, roofs and chain fencing.

Also helps to identify intruders by marking them with it's special identifying agent.

Preparation

Ensure all surfaces are thoroughly clean from loose or flaking material. High gloss or very smooth surfaces should be thoroughly abraded, scraped and sanded to assist adhesion (use a wire brush or 90-100 grade sandpaper). Any absorbent or bituminous surfaces should be sealed with a suitable primer or sealer and any new unpainted surfaces should be primed with a surface primer (eg. on wood use a wood primer, on metal use a metal primer such as Zinc Phosphate).

Application

Apply Bond It **ANTI-CLIMB PAINT** with a short haired brush or industrial mitt, smoothing to a uniform finish, to 1-2mm thickness. Do not apply more than 3mm and do not thin the product.

Wear gloves during application and only apply to areas above arms reach (see note).

Note: *ANTI-CLIMB PAINT is not recommended for use on surfaces in areas which are subject to legitimate daily contact. It is also recommended that it not be applied to sills, fall pipes, walls, etc., within 7ft of the ground level, and it's presence should be clearly identified to the public (e.g. warning notices).*

Limitations

ANTI-CLIMB PAINT operates best at temperatures not exceeding 30°C.

Container Size

2Kg tins.

Cleaning of Tools

Use white spirit or turpentine substitute.

Storage Conditions

12 months shelf life when stored in well ventilated, dry conditions between 5-25°C. Keep away from sources of heat and ignition and out of direct sunlight.

Disposal of Containers

Do not leave empty containers where residue could be harmful to children, animals or the environment. Replace lids and remove any containers to a central disposal point in accordance with local regulations.

In the event of spillage remove all sources of ignition, ventilate the area, remove people from confined areas. Material should be mopped up immediately with an inert absorbent material such as sand or sawdust.

Health & Safety

- ◆ Flammable - remove all sources of ignition. Do not smoke.
- ◆ Avoid eye contact. In the event of contact wash with running water for 15 minutes and seek medical attention. Wear goggles.
- ◆ Ensure good ventilation - harmful by inhalation. Wear vapour protection mask.
- ◆ Do not ingest. Do not induce vomiting if swallowed. Seek medical attention.
- ◆ Avoid prolonged contact with skin, can cause irritation. Wear gloves.
- ◆ Thoroughly wash hands with soap and water after use.
- ◆ Keep out of reach of children.
- ◆ See separate material safety data sheet for full handling, use and storage.

Specification Summary

Flammability	Flammable
Flash Point	Above 32°C
Appearance	Grease like paint
Specific Gravity	approx. 0.98 @ 20°C
Typical Total Solids	94.3% by weight
Coverage	0.5-1m ² per 2Kg unit

Container Sizes:

Colour:	Black
Code:	BDACPBL1
Size:	2Kg

The data presented in this leaflet are in accordance with the present state of our knowledge, but do not absolve the user from carefully checking all supplies immediately on receipt. We reserve the right to alter product constants within the scope of technical progress or new developments. The recommendations made in this leaflet should be checked by preliminary trials because of conditions during processing over which we have no control, especially where other companies raw materials are also being used. The recommendations do not absolve the user from the obligation of investigating the possibility of infringement of third parties rights and, if necessary clarifying the position. Recommendations for use do not constitute a warranty, either expressed or implied, of the fitness or suitability of the products for a particular purpose.