



Never compromise on quality!

Published: May 2007

RAIN-MATE

All Weather General Purpose Sealant

Description

A water repellent, general purpose sealant, based on SBR rubber. It has excellent adhesion to all surfaces, even when damp.

Uses

Bond It **RAIN-MATE** is a permanently flexible, water repellent and UV resistant, paintable sealant that will not crack or slump.

It suitable for use on brick, concrete, stone, all metals, painted or bare wood, glass, vinyl and most plastics. It is also compatible with bitumen and asphalt for roof repairs in damp conditions.

It is ideal for sealing doors, windows, roofs, cladding and vehicle bodies.

Application

Primers are not usually required.

Rust, etc, should be removed to give as sound a surface as possible. For application in damp conditions remove any standing water and residual dirt and dry the surface as well as possible with cloths or paper towels before applying sealant. Apply the sealant in a normal fashion ensuring there is sufficient sealant present to accommodate any future joint movement (25% of sealant width). Allow 24 hours before painting.

Cleaning

Clean tools immediately using Bond It uPVC Solvent Cleaner.

Limitations

Not for use on expanded polystyrene, polycarbonate, plastic roof lights or other solvent sensitive surfaces. Do not apply at over 60°C or on surfaces which exceed 80°C in use.

Container Size

EU3 plastic cartridge.

Colours

RAIN-MATE comes in 4 colours: black, clear, brown and white.

Shelf Life

Minimum 12 months in unopened cartridge.

Storage Conditions

Store in cool, dry conditions.

Disposal of Containers

Do not leave empty containers where residue could be harmful to children, animals or the environment. Remove any containers to a central disposal point in accordance with local regulations.

Health & Safety

- ◆ Flammable.
- ◆ Avoid eye contact.
- ◆ Avoid prolonged contact with skin.
- ◆ Thoroughly wash hands with soap and water after use.
- ◆ Keep out of reach of children.
- ◆ Some people are more sensitive to chemical products than others. If irritation occurs discontinue use.
- ◆ See separate material safety data sheet for full handling, use and storage.

Specification Summary

Flammability	Flammable
Skinning Time	15 minutes
Full Cure	24 hours before painting, full cure dependent on depth
Joint Movement	Plus or minus 25%
Specific Gravity	0.95
Flash Point	Approx 25°C
Viscosity	Approx. 800 poise @ 25°C
Evaporation Rate	<25
Solvent Content	23%

Container Sizes:

Code:	BDAWCL	BDAWSWH	BDAWSBL	BDAWSBR
Colour:	Clear	White	Black	Brown
Size:	EU3	EU3	EU3	EU3

The data presented in this leaflet are in accordance with the present state of our knowledge, but do not absolve the user from carefully checking all supplies immediately on receipt. We reserve the right to alter product constants within the scope of technical progress or new developments. The recommendations made in this leaflet should be checked by preliminary trials because of conditions during processing over which we have no control, especially where other companies raw materials are also being used. The recommendations do not absolve the user from the obligation of investigating the possibility of infringement of third parties rights and, if necessary clarifying the position. Recommendations for use do not constitute a warranty, either expressed or implied, of the fitness or suitability of the products for a particular purpose.

BOND IT
Unit G16 River Bank Way, Lowfields Business Park, Elland, West Yorkshire HX5 9DN.
Telephone: +44 (0)1422 315300 Fax +44 (0)1422 315310
Email: sales@bond-it.co.uk Website: www.bond-it.co.uk

