



Never compromise on quality



FLOOR TILE GROUT

Water Resistant Grouting Compound

Description

A grey, cement-based, polymer modified wide joint filling compound for tile joints from 3mm up to 12mm wide around all types of ceramic floor tiles. Can be used in interior and exterior applications. Conforms to EN 13888:2002 Type CG Class 1.

Uses

FLOOR TILE GROUT is formulated to provide a flowable, readily compactable grouting slurry, which can be easily applied across all types of ceramic tiled surfaces. **FLOOR TILE GROUT** will dry to a hard, durable, water resistant finish, suitable for interior and exterior applications, including swimming pools.

Preparation

Check that all the tiles are securely fixed and that the tile adhesive has thoroughly dried before applying any load or pressure to the tiled surface. Allow a minimum of 12-24 hours when using standard setting adhesives and ready mixed tile adhesives, or 2-3 hours when using fast setting adhesives. Ensure all joints are a maximum of 3mm wide and they are raked clear of any excess adhesive residues to allow an even and consistent depth of grout to be applied in all areas. It is recommended that current best practice e.g. current TTA or COP guidelines are always followed.

Mixing

FLOOR TILE GROUT powder should be added to clean water, approximately 10Kg powder to 3L of water in a clean container and mixed to a smooth, creamy, lump-free consistency, preferably with a mechanical mixer. Allow to stand for 3-5 minutes, re-mix briefly, and use within 1 hour depending on site temperature and conditions.

Part-used grout should never be "freshened up" by adding more water, discard any grout once it appears to lose workability.

Application

Using a grouting tool, sponge or squeegee, work the mixed grout thoroughly into the tile joints ensuring the joints are completely filled. Remove excess grout from the face of tiles with a damp sponge or cloth. Use a suitable tool to compact the grout into joints. After initial hardening of the grout, clean the tile surface using a clean dampened sponge working diagonally across the grout lines. Allow the grout to harden sufficiently to prevent removal from the joints when cleaning (normally between 1 and 2 hours). Once the grout is set polish

the tiles with a soft cloth. Clean tools after use with warm water.

Drying Time

Final set will occur between 24-48 hours. Cement based products will take longer to harden and set at lower temperatures and should not be used below 5°C. Light foot traffic: after 12-24 hours; Full traffic: after 24-48 hours (dependant on site conditions).

In exterior conditions, it is essential to provide protection from all extremes of climate for as long as possible during and after grouting has been completed (a minimum of 72 hours is recommended).

Open Time

Open time of the exposed adhesive bed is approx. 20 minutes, dependant on conditions. Pot life approx 60 minutes @ 20°C.

Limitations

Use mixed material within 1 hour. Do not re-mix grout that is starting to set by adding extra water. All tile surfaces should be checked before starting to ensure colour staining of porous surfaces or scratching of glazed surfaces will occur during grouting. Slight colour variation may occur between batches. Colour variation will occur under different mixing and/or site conditions. Swimming pools should not be filled for 3 weeks after grouting. Not to be used in applications prone to movement.

Coverage

This will vary depending on the tile size, joint depth and width. Approximately 1Kg of **FLOOR TILE GROUT** will grout 2m² of 300 x 300mm tiles with a 5mm joint depth.

Cleaning

Tools should be washed with water immediately after use with warm water.

Disposal of Containers

Do not leave empty containers where residue could be

harmful to children, animals or the environment. Remove any bags or material to a central disposal point in accordance with local regulations.

Storage Conditions

Store in original, unopened sacks, off the ground, in cool, dry conditions and away from excessive draughts. **Shelf life:** 10Kg paper sack: use within 6 months of the date of packing shown on the bag. 3Kg plastic sack: use within 12 months of the date of packing shown on the bag.

Health & Safety

Contains cement. Contains Chromium VI.

Risk of serious damage to eyes. Contact with wet product - or dry powder contact with body fluids, such as sweat or eye fluid, may cause irritation, dermatitis or burns. May produce an allergic reaction. Wear suitable protective clothing, gloves,

overalls and eye/ face protection. After contact with skin, wash off immediately with plenty of clean water. Use a dust mask if excessive dust is unavoidable. Keep out of reach of children. In case of contact with eyes, irrigate thoroughly with clean, running water for at least 15 minutes and seek medical attention.

Note: This information is for general guidance only, since site conditions and labour are beyond our control. It is recommended that users make their own tests to determine suitability, especially when using natural stone, porous or unglazed tiles as these are prone to absorption of grout fines. Our liability is limited to replacement or refund of cost of product. All tiling should be carried to current best practice, including British Standards and TTA Guidance documents. Safety data sheet available for the professional user upon request. Comprehensive technical data sheet available on www.bond-it.co.uk

Specification Summary

Flammability	Non Flammable
Application Temperature	5-30°C
Working Time	1 Hour
Joint Width	3-12mm
Compressive Strength	> 15MPa
Flexural Strength	>2.5 MPa
Shrinkage	< 3mm/m
Pot Life	Approximately 60 minutes
Setting Time	12- 24 hours (dependent on conditions)
pH @ 20°C	12-13
Solubility in Water	> 2g/l
Hazard Information	Irritant; Consult safety data sheet before use

Container Sizes

Code:	BDFTG10	BDFTG3
Size:	10Kg	3Kg
Barcode:	5060021363497	5060021369543

The data presented in this leaflet are in accordance with the present state of our knowledge, but do not absolve the user from carefully checking all supplies immediately on receipt. We reserve the right to alter product constants within the scope of technical progress or new developments. The recommendations made in this leaflet should be checked by preliminary trials because of conditions during processing over which we have no control, especially where other companies raw materials are also being used. The recommendations do not absolve the user from the obligation of investigating the possibility of infringement of third parties rights and, if necessary clarifying the position. Recommendations for use do not constitute a warranty, either express or implied, of the fitness or suitability of the products for a particular purpose.



Certificate Number: 6152
ISO 9001
ISO 14001



BOND IT
Unit G16 River Bank Way, Lowfields Business Park,
Elland, West Yorkshire HX5 9DN.
Telephone: +44 (0)1422 315300 Fax +44 (0)1422 315310
Email: sales@bond-it.co.uk Website: www.bond-it.co.uk



V3 23/9/13