



Never compromise on quality!



DRIVE ALIVE PATIOSEAL

Sealer for protecting paths and patios

Description

A solvent-free, acrylic liquid used to seal and protect patios, paths, natural stone, concrete and block paving from sunlight, water, oil, petrol and fungal/moss growth.

Uses

Protects block paving driveways and pathways and patios against water penetration as well as spillages of contaminants, such as oil and grease. It will also deter dirt and grime build-up and will enhance both the present colour of the paths and greatly extend the lifespan of the driveway.

Benefits:

- Solvent-free formulation - low odour.
- Facilitates easier cleaning.
- Improves water resistance and UV resistance.
- Retards mould growth.

Preparation

Remove organic growth/ lichens, etc. that may be present. For best results use Bond It MOULD STOP, PATIO BLASTER or ORGANIC CLEANER; refer to the appropriate data sheet. Wash all debris away and ensure the surface is dry and free from oil, grease, dust and loose material that may hinder adhesion.

Application

Application

Bond It **PATIOSEAL** is ready to use, and does not require diluting. We advise that you test this product on a small inconspicuous area prior to use to check compatibility. SHAKE WELL BEFORE USE. Ensure that the surface is completely dry. Apply a single coat using either a brush, roller or squeegee, ensuring no pooling or ponding occurs. Allow 3-4 hours drying time before trafficking the area. Application temperature between 5°C and 30°C. Colder humid conditions will slow drying times.

Limitations

Do not apply Bond It **PATIOSEAL** to wet surfaces or in conditions of high humidity. Do not use when rain is forecast (protect from rain until dry). Do not apply to non-porous surfaces. Keep children and pets away from treated areas until fully cured. Do not allow any run off to contaminate drains, waterways or plants.

It is the users responsibility to determine suitability for use. If in doubt, consult our Technical Department for further details. Areas treated with this product can be cleaned with warm water and detergent or Bond It MOULD STOP. Do not use acid based cleaners, as these will

remove/dicolour the product. Also avoid using power washers. It is advisable to use this product during warmer/drier months (April - October).

Storage Conditions

Store in cool, dry conditions in original sealed container. Keep away from direct sunlight and protect from frost.

Shelf Life

24 months when stored according to manufacturers instructions.

Coverage

A single coat application will cover approximately 10-15m² per litre depending on surface porosity.

Disposal of Containers

Do not leave empty containers where residue could be harmful to children, animals or the environment. Replace lids and remove any containers to a central disposal point in accordance with local regulations.

Health & Safety

- ◆ Product presents a low hazard in correct use.
- ◆ Avoid eye contact. In the event of contact irrigate eyes immediately with plenty of cold, clean water for 15 minutes and seek medical attention.
- ◆ Do not ingest. In the event of ingestion, do not induce vomiting, drink plenty of water and seek medical attention.
- ◆ Thoroughly wash hands with soap and water after use.
- ◆ Keep out of reach of children.
- ◆ Some people are more sensitive to chemical products than others. If irritation occurs discontinue use.
- ◆ See separate material safety data sheet for full handling, use and storage.

Application Notes

It is necessary to seal paviours prior to the application of any pointing or jointing compound. Some compounds have the capability of staining porous paving materials.

*Ensure **PATIOSEAL** has completely cured prior to pointing. Do not apply **PATIOSEAL** to any uncured wet pointing or to any dry mix cement compound.*

If applying **PATIOSEAL** to new pavements ensure a sufficient period of weathering (as recommended by the paving manufacturer) has elapsed in order to avoid efflorescence.

Pavements can be resealed using a single coat of **PATIOSEAL**, if it is necessary. This can be determined by a small porosity test to the surface in an inconspicuous area. We suggest an area be subjected to a sprinkling of water via a watering can with rose attachment, if the water beads then a further application is not necessary as the seal is still intact. However, if the water is

absorbed by the patio surface re-application can be performed. For patios with unknown treatments we would also suggest using the same test method to determine suitability. Adverse reactions can be caused if **PATIOSEAL** is used over other existing sealers or treatments so should be avoided at all times. Avoid over application in all circumstances.

Specification Summary

Physical Properties	Milky white liquid, non flammable, zero VOC, water miscible.
Application:	STIR WELL BEFORE USE. Do not apply to wet surfaces, in high humidity or when rain is expected
Application Temperature Range	5°C to 30°C
Drying Time	1-2 hours in warm, sunny conditions
Coverage Rate	40 - 60m ² per 4 litre container
Cleaning	Rinse then wash brushes and rollers in warm, soapy water
Shelf Life	2 years

Container Sizes

Code:	BDH061	BDH063
Size:	5L	25L
Barcode:	5060021363954	5060021364920

The data presented in this leaflet are in accordance with the present state of our knowledge, but do not absolve the user from carefully checking all supplies immediately on receipt. We reserve the right to alter product constants within the scope of technical progress or new developments. The recommendations made in this leaflet should be checked by preliminary trials because of conditions during processing over which we have no control, especially where other companies raw materials are also being used. The recommendations do not absolve the user from the obligation of investigating the possibility of infringement of third parties rights and, if necessary clarifying the position. Recommendations for use do not constitute a warranty, either express or implied, of the fitness or suitability of the products for a particular purpose.



Certificate Number: 6152
ISO 9001
ISO 14001



BOND IT
Unit G16 River Bank Way, Lowfields Business Park,
Elland, West Yorkshire HX5 9DN.
Telephone: +44 (0)1422 315300 Fax +44 (0)1422 315310
Email: sales@bond-it.co.uk Website: www.bond-it.co.uk



V5 09/07/14
Supersedes: V4 18/6/14