



Never compromise on quality!



LAMI-MATE

Advanced Flexible Sealant And Gap-Filler For Timber And Laminates

Description

An polymer enhanced, flexible sealant and gap-filler designed for sealing all tongue and groove laminate flooring. When cured it can be overpainted, varnished or wood stained if required. Conforms to BS EN 15651-1:2012.

Uses

Bond It LAMII-MATE stays permanently flexible and can be used for sealing all types of laminate and hardwood flooring. It is ideal for draught proofing around timber flooring to provide an effective dust and air tight seal. It can also be used for sealing around all types of fitted furniture i.e. bedroom and kitchen fittings, laminate worktops, etc. LAMI-MATE is also suitable for sealing glass panels into kitchen unit doors.

Preparation

Ensure all surfaces are clean, dry and free from grease or any contaminants that may hinder adhesion.

Application

Apply using a standard sealant gun with the nozzle cut at an angle of 45°, and to an opening slightly larger than the joint to be sealed. Smooth down using a slightly wetted spatula, piece of wood or finger. Tools and excess sealant can be cleaned with a damp sponge.

If overpainting or staining allow sealant to cure fully before painting.

Limitations

Do not use in conjunction with bitumen or asphalt. For perimeter use only, do not use in areas subject to mechanical abrasion. Do not attempt to sand down.

Caution: The colour on application will be different to the colour achieved when fully cured.

Container Size

EU3 plastic cartridge.

Colours

LAMI-MATE comes in 3 colours: beech, pine and oak.

Shelf Life

24 months in unopened cartridge.

Storage Conditions

Store in cool, dry conditions. Avoid temperatures below 5°C and protect from frost.

Disposal of Containers

Do not leave empty containers where residue could be harmful to children, animals or the environment. Remove any containers to a central disposal point in accordance with local regulations.

Health & Safety

- ◆ Avoid eye contact.
- ◆ Avoid prolonged contact with skin.
- ◆ Thoroughly wash hands with soap and water after use.
- ◆ Keep out of reach of children.
- ◆ See separate material safety data sheet for full handling, use and storage.

Specification Summary

Tooling Time	5-10 mnutes
Full Cure	24-48 hours dependant on size of bead and temperature
Specific Gravity	1.04-1.08
ph	8.10 - 8.70
Solubility in Water	Miscible when uncured
Flammability	Non flammable
Flash Point	N/A Water based

Container Sizes:

Colour:	Oak	Pine	Beech
Code:	BDLSOK	BDLSPN	BDLSBC
Size:	EU3	EU3	EU3
Barcode:	5060021362667	5060021362643	5060021362650



BOND IT	
G16 River Bank Way, Lowfields Business Park, Elland, West Yorkshire. HX5 9DN	
14	
EN15651-1:2012 F INT Facade sealant for interior use.	
Reaction to fire	F
Release of chemicals	None
Resistance to flow	≤ 5mm
Loss of volume	≤45%
Tensile properties: Elongation at break 23°C	≥25%
Durability	Pass

The data presented in this leaflet are in accordance with the present state of our knowledge, but do not absolve the user from carefully checking all supplies immediately on receipt. We reserve the right to alter product constants within the scope of technical progress or new developments. The recommendations made in this leaflet should be checked by preliminary trials because of conditions during processing over which we have no control, especially where other companies raw materials are also being used. The recommendations do not absolve the user from the obligation of investigating the possibility of infringement of third parties rights and, if necessary clarifying the position. Recommendations for use do not constitute a warranty, either expressed or implied, of the fitness or suitability of the products for a particular purpose.



Certificate Number: 6152
ISO 9001
ISO 14001



BOND IT
Unit G16 River Bank Way, Lowfields Business Park, Elland, West Yorkshire HX5 9DN.
Telephone: +44 (0)1422 315300 Fax +44 (0)1422 315310
Email: sales@bond-it.co.uk Website: www.bond-it.co.uk



V2 09/07/2014