



Never compromise on quality!

PRIMER & FLEXIBLE ADMIX

All-Purpose Ceramic Tile Adhesive Primer And Flexibilising Admixture

Description

A specially formulated acrylic dispersion for use as a primer prior to tiling or as an additive to cement based tiling products to improve adhesion and flexibility.

Uses

As a primer: to prepare and stabilise porous and dusting surfaces prior to tiling and to improve adhesion on difficult substrates, such as vinyl tiles, timber, asphalt and terrazzo, etc. Also prevents swelling of timber.

As an admixture: to improve the flexibility and adhesion of cement based adhesives and grouts in situations subject to slight movement or vibration.

Preparation

For use as a primer: surfaces must be clean, structurally sound, dry, flat and free from dust, oil, grease, old polish and any other contamination that may prevent adhesion.

For use as an admix: For surface preparation refer to individual products recommendations.

Application

As a primer: Shake the bottle before use. Apply a single coat of **PRIMER**, to the substrate ensuring complete coverage. Allow to become tack free before commencing tiling. If left without tiling overnight a second coat should be applied. Apply adhesive and tiles as normal practice.

As an admix: add up to 5 Litres per 20Kg bag of adhesive or grout. High dosages may effect the setting time of some products.

Coverage

As a primer: 1 Litre will cover 5-10m² dependant on porosity of surface.

As an admix: Up to 5 Litres per 20Kg of cement based adhesive or grout.

Storage Conditions

Store in cool, dry conditions. Protect from frost, high temperatures and direct sunlight. Use within 12 months.

Disposal of Containers

Do not leave empty containers where residue could be harmful to children, animals or the environment. Replace lids and remove any containers to a central disposal point in accordance with local regulations.

Cleaning

Clean tools immediately with soap and water before the product dries.

Health & Safety

- ◆ Low hazard product, safe in normal use.
- ◆ Wear safety glasses and gloves during application.
- ◆ If product enters eyes wash immediately with plenty of cold water and seek medical attention.
- ◆ After contact with skin wash immediately with soap and water.
- ◆ Keep out of reach of children.
- ◆ Do not ingest.
- ◆ Some people are more sensitive to chemical products than others, if irritation occurs discontinue use.

Specification Summary

Appearance	Milky White Liquid capable of florescence
Flammability	Non Flammable
pH	approximately 8
Solubility in water	Soluble
Boiling Point	100°C (water)

Container Sizes

Code:	BDTAP	BDTAP1
Size:	5L	1L
Barcode:	50600213633	5060021369437

The data presented in this leaflet are in accordance with the present state of our knowledge, but do not absolve the user from carefully checking all supplies immediately on receipt. We reserve the right to alter product constants within the scope of technical progress or new developments. The recommendations made in this leaflet should be checked by preliminary trials because of conditions during processing over which we have no control, especially where other companies raw materials are also being used. The recommendations do not absolve the user from the obligation of investigating the possibility of infringement of third parties rights and, if necessary clarifying the position. Recommendations for use do not constitute a warranty, either express or implied, of the fitness or suitability of the products for a particular purpose.



Certificate Number: 6152
ISO 9001
ISO 14001



BOND IT
Unit G16 River Bank Way, Lowfields Business Park,
Elland, West Yorkshire HX5 9DN.
Telephone: +44 (0)1422 315300 Fax +44 (0)1422 315310
Email: sales@bond-it.co.uk Website: www.bond-it.co.uk



V2 04/06/13