

Construction Products Regulations (EU) 305 2011


DECLARATION OF PERFORMANCE DOP BDLA5

- 1 Identification Code: Bond-It LA5 LMA Silicone
2. Batch Identification: By batch number – see print on packaging
3. Intended uses: **F EXT-INT** Façade Sealant for Exterior and Interior Use. **G 25LM** Glazing Silicone.
4. Manufacturer: Seal It Services t/a Bond It
Unit G16 River Bank Way
Lowfields Business Park
Elland
West Yorkshire
HX5 9DN
5. Authorised Representative: Not applicable
6. System of assessment and Verification of constancy: System 3
7. Notified Body: NB01213
8. European Technical Assessment: Not Applicable
9. Declared performance:

ESSENTIAL CHARACTERISTIC	DECLARED PERFORMANCE	HARMONISED STANDARD
Reaction to Fire	Class E	
Release of Chemicals	None	See MSDS
Water Tightness and Air Tightness as determined by:		BS EN 15651-1,2:2012
Resistance to Flow	≤3mm	Conditioning method A
Loss of Volume	≤10%	Tested on aluminium without primer, glass without primer
Tensile properties after water immersion	NF	
Durability	Pass	

10. The performance of the product identified in points 1 and 2 is in conformity with the declared performance in point 9.

Signed for and on behalf of the manufacturer by:



Phil Radford
Technical Manager
Elland
26 June 2014