

## Construction Products Regulations (EU) 305 2011


### DECLARATION OF PERFORMANCE DOP BDL5

- 1 Identification Code: Bond-It Lami-mate Timber & Laminate Sealant  
2. Batch Identification: By batch number – see print on packaging  
3. Intended uses: **F INT** Façade Sealant for Interior Use  
4. Manufacturer: Seal It Services t/a Bond It  
Unit G16 River Bank Way  
Lowfields Business Park  
Elland  
West Yorkshire  
HX5 9DN  
5. Authorised Representative: Not applicable  
6. System of assessment and Verification of constancy: System 4  
7. Notified Body:  
8. European Technical Assessment: Not Applicable  
9. Declared performance:

ESSENTIAL CHARACTERISTIC	DECLARED PERFORMANCE	HARMONISED STANDARD
Reaction to Fire	Class F	
Release of Chemicals	None	See MSDS
Water Tightness and Air Tightness as determined by:		BS EN 15651-1:2012 Conditioning method A Tested on Mortar M2 without primer
Resistance to Flow	≤5mm	
Loss of Volume	≤45%	
Tensile properties: Elongation at break at 23°C	≥25%	
Durability	Pass	

10. The performance of the product identified in points 1 and 2 is in conformity with the declared performance in point 9.

Signed for and on behalf of the manufacturer by:



Phil Radford  
Technical Manager  
Elland  
26 June 2014