

Construction Products Regulations (EU) 305 2011

DECLARATION OF PERFORMANCE
DOP WP100

- | | |
|--|---|
| 1 Identification Code: | Bond-It WP100 Oxime Silicone |
| 2. Batch Identification: | By batch number – see print on packaging |
| 3. Intended uses: | F EXT-INT Façade Sealant for Exterior and Interior Use. G 25LM Glazing Sealant. Sanitary Sealant. |
| 4. Manufacturer: | Seal It Services t/a Bond It
Unit G16 River Bank Way
Lowfields Business Park
Elland
West Yorkshire, HX5 9DN |
| 5. Authorised Representative: | Not applicable |
| 6. System of assessment and Verification of constancy: | System 3 |
| 7. Notified Body: | 0757 |
| 8. European Technical Assessment: | Not Applicable |
| 9. Declared performance: | |

ESSENTIAL CHARACTERISTIC	DECLARED PERFORMANCE	HARMONISED STANDARD
Reaction to Fire	Class E	
Release of Chemicals	None	See MSDS
Water Tightness and Air Tightness as determined by:		BS EN 15651-1,2:2012 Conditioning method B Tested on Mortar M1 without primer, Glass without primer, Aluminium without primer
Resistance to Flow	≤3mm	
Loss of Volume	≤10%	
Tensile properties at maintained extension	Pass	
Tensile Properties – secant modulus	Pass	
Adhesion/cohesion at variable temperature	Pass	
Adhesion/cohesion after water immersion.	Pass	
Adhesion/cohesion after exposure to heat, water and artificial light	Pass	
Elastic Recovery	>70%	
Durability	Pass	

10. The performance of the product identified in points 1 and 2 is in conformity with the declared performance in point 9.

Signed for and on behalf of the manufacturer by:



Phil Radford
Technical Manager
Elland
26 June 2014