



Never compromise on quality!

# PC100 INHIBITOR

## Liquid

### Description

*A high performance inhibitor against formation of scale, rust corrosion, hydrogen gassing, microbiological growth and boiler noise.*

### Uses

**PC100 INHIBITOR** is suitable for all metals including aluminium. Once added PC100 does not need to be replaced unless the system is drained down.

### Application

Filling the system: Open systems should be dosed via the filling and expansion tank. If system is full, draining at a low point should be carried out to ensure product enters the circulatory system. Sealed systems should be filled via filling loop or a drained radiator.

Dosage: PC100 for optimum efficiency should be dosed @1% of system volume. Generally 1 bottle contains enough chemical for a typical system with a 14.5Kw Boiler (50,000 Btu/hr) domestic hot water cylinder and up to 10 radiators. For larger systems an extra bottle will be required - overdosing will not cause any problems or detrimental affects to the system.

Please note: where a thermal storage appliance is fitted allowance must be made for the extra volume of primary water. The concentration can be checked with a conductivity meter.

### LIMITATIONS

**DO NOT ADD TO PRIMATIC SYSTEM.**

### Storage Conditions

Store in cool, dry conditions in tightly sealed container. Store above +5°C and below +30°C. Do not allow to freeze.

### Shelf Life

12 months in original, unopened containers.

### Disposal of Containers

Do not leave empty containers where residue could be harmful to children, animals or the environment. Replace lids and remove any containers to a central disposal point in accordance with local regulations.

### Health & Safety

- ◆ Low hazard product - safe in normal use.
- ◆ Wear gloves, wash splashes off skin with soap and water.
- ◆ If product enters eyes wash immediately with copious amounts of cold water.
- ◆ Keep out of reach of children.
- ◆ Do not ingest.
- ◆ Some people are more sensitive to chemical products than others. If irritation occurs, discontinue use.

Always follow the manufacturer's recommendations when using this product. It is the users responsibility to determine suitability. Safety data sheet available on request for professional user.

PLUMBERS COMPLETE RANGE

## Specification Summary

Flashpoint	None
Appearance	Light coloured
Odour	Faint
Specific Gravity	1.05
pH	7.3

## Container Sizes

<b>Code:</b>	BDPC100
<b>Size:</b>	1L
<b>Barcodes:</b>	5060021367495

*The data presented in this leaflet are in accordance with the present state of our knowledge, but do not absolve the user from carefully checking all supplies immediately on receipt. We reserve the right to alter product constants within the scope of technical progress or new developments. The recommendations made in this leaflet should be checked by preliminary trials because of conditions during processing over which we have no control, especially where other companies raw materials are also being used. The recommendations do not absolve the user from the obligation of investigating the possibility of infringement of third parties rights and, if necessary clarifying the position. Recommendations for use do not constitute a warranty, either express or implied, of the fitness or suitability of the products for a particular purpose.*