



Never compromise on quality!

PC300 UNICLEAN

Universal Cleaner

Description

A powerful universal cleaner and passivater for new central heating systems or systems up to 6 months old.

Uses

PC300 UNICLEAN is suitable for all metals including aluminium; no neutralisation required.

Application

Filling the system: Open systems should be dosed via the filling and expansion tank. Adequate draining from a low point is necessary to ensure product enters the system. Closed systems should be dosed via filling loop or a partially drained radiator. If the system is empty add at any suitable point prior to filling.

Cleaning: Circulate the system containing the cleaner for at least one hour. Warming the water by running the boiler on low will aid the process. Drain the system at all drain points and then flush through until water runs clear. When re-filling system dose with PC100 or 200 INHIBITOR.

Dosage: PC300 should be dosed @ 1% of system for maximum performance. This is the volume of a system with a 14.5Kw Boiler (50,000 Btu/hr). Larger systems will require more cleaner pro rata. Overdosing will not cause any problems or detrimental affects to the system.

Please note: where a thermal storage appliance is fitted allowance must be made for the extra volume of primary water. The concentration can be checked with a conductivity metre.

LIMITATIONS

DO NOT ADD TO PRIMATIC SYSTEM.

Storage Conditions

Store in cool, dry conditions in tightly sealed container. Do not allow to freeze.

Shelf Life

12 months in original, unopened containers.

Disposal of Containers

Do not leave empty containers where residue could be harmful to children, animals or the environment. Replace lids and remove any containers to a central disposal point in accordance with local regulations.

Health & Safety

- ◆ Low hazard product - safe in normal use.
- ◆ Wear gloves, wash splashes off skin with soap and water.
- ◆ If product enters eyes wash immediately with copious amounts of cold water.
- ◆ Keep out of reach of children.
- ◆ Do not ingest.
- ◆ Some people are more sensitive to chemical products than others. If irritation occurs, discontinue use.

Always follow the manufacturer's recommendations when using this product. It is the users responsibility to determine suitability. Safety data sheet available on request for professional user.

Specification Summary

Appearance	Pale orange liquid
Odour	None
Specific Gravity	Approx 1
pH	Approx 4-5
Vapour Pressure	2.14 KPa (25°C)

Container Sizes

Code:	BDPC300
Size:	1L
Barcode:	5060021367488

The data presented in this leaflet are in accordance with the present state of our knowledge, but do not absolve the user from carefully checking all supplies immediately on receipt. We reserve the right to alter product constants within the scope of technical progress or new developments. The recommendations made in this leaflet should be checked by preliminary trials because of conditions during processing over which we have no control, especially where other companies raw materials are also being used. The recommendations do not absolve the user from the obligation of investigating the possibility of infringement of third parties rights and, if necessary clarifying the position. Recommendations for use do not constitute a warranty, either express or implied, of the fitness or suitability of the products for a particular purpose.



Certificate Number: 6152
ISO 9001
ISO 14001



BOND IT
Unit G16 River Bank Way, Lowfields Business Park,
Elland, West Yorkshire HX5 9DN.
Telephone: +44 (0)1422 315300 Fax +44 (0)1422 315310
Email: sales@bond-it.co.uk Website: www.bond-it.co.uk



V3 3/12/12