



Never compromise on quality!

PC900 PIPE JOINTING COMPOUND

Description

A non-toxic, pipe jointing compound which simply acts as a sealant and lubricant enabling pipe threads to be screwed tight.

Uses

PC900 PIPE JOINTING COMPOUND can be used for use on pipework carrying cold and hot water, low saturated steam, 1st family gases (excluding coal gas) and 2nd family gases.

Preparation

Ensure all threads are clean and free from burrs, grease or other contaminants.

Application

Apply compound using a spatula, applying a liberal coat evenly over the male thread, making sure that the threads are completely filled. The compound also acts as a lubricant which helps pipe threads to be screwed tight. Suitable for use with hemp thread.

Conforms to EN 751-2:1997 Part 2 Class A for use with hot and cold water (non-potable duties), natural gas and low pressure steam up to a 7 bar pressure and temperatures up to 150°C.

Limitations

Not recommended for potable drinking water applications.

Storage Conditions

Store in cool, dry conditions in tightly sealed container. Store between a temperature of +5°C and +20°C.

Shelf Life

2 years in original, unopened containers.

Container

400g plastic tub.

Disposal of Containers

Do not leave empty containers where residue could be harmful to children, animals or the environment. Replace lids and remove any containers to a central disposal point in accordance with local regulations.

Health & Safety

- ◆ Do not ingest.
- ◆ Wash hands thoroughly after use.
- ◆ Take care when using this product.
- ◆ Seek medical advice if you suffer any adverse reactions from using this product.
- ◆ Keep out of reach of children.

Always follow the manufacturer's recommendations when using this product. It is the user's responsibility to determine suitability. Safety data sheet available on request for professional user.

Specification Summary

Colour	Buff
Bulk Density	1.65g/ml
Flashpoint	Non flammable
Temperature Resistance	150°C
Pressure Test	Cold Water working pressure of 7 bar. Hot water working pressure of 7 bar and working temp of up to 100°C. 1st (exc. coal based) & 2nd family gases working pressure of 7 bar and a working temp of 150°C. Note: these are typically referred to as Town Gas & Natural gas respectively Low pressure saturated steam up to working pressure of 7 bar.

Container Sizes

Code:	BDPC900
Size:	400g
Barcode:	5060021367518

The data presented in this leaflet are in accordance with the present state of our knowledge, but do not absolve the user from carefully checking all supplies immediately on receipt. We reserve the right to alter product constants within the scope of technical progress or new developments. The recommendations made in this leaflet should be checked by preliminary trials because of conditions during processing over which we have no control, especially where other companies raw materials are also being used. The recommendations do not absolve the user from the obligation of investigating the possibility of infringement of third parties rights and, if necessary clarifying the position. Recommendations for use do not constitute a warranty, either express or implied, of the fitness or suitability of the products for a particular purpose.



Certificate Number: 6152
ISO 9001
ISO 14001



BOND IT
Unit G16 River Bank Way, Lowfields Business Park,
Elland, West Yorkshire HX5 9DN.
Telephone: +44 (0)1422 315300 Fax +44 (0)1422 315310
Email: sales@bond-it.co.uk Website: www.bond-it.co.uk



V2 20/08/14