



Never compromise on quality!

WATERSEAL

Masonry Waterproofer

Description

A premium waterseal designed to repel water from masonry work which allows walls to breathe, reducing the risk of damage caused by water and frost.

Uses

Bond It **WATERSEAL** is used as a masonry waterproofer suitable for use on brick, stone and concrete. It protects against water and frost, providing a breathable coating which does not change the physical appearance of a building.

A secondary benefit of the product is to repel waterborne dirt and resist fungal growth as well as help reducing heating costs as energy is not wasted in drying out wet walls.

Preparation

Ensure all surfaces are dry and free from dirt, mosses and lichens. For stubborn mosses and lichens use Bond It **MOULD & MILDEW WASH**. Allow a minimum of 24 hours for fresh pointing to dry before application.

Application

Apply using a low pressure spray (non-atomising) or brush at a rate of 3m² per litre for porous stone and 5m² per litre for hard brick, allowing 6 hours to dry before applying a second coat. Always apply with a smooth action starting at the top and working your way down the wall. Care should be taken not to splash or mist cars, windows, painted surfaces, plants and ponds. Two coats are recommended for best results, however more coats can be applied.

Limitations

Bond It **WATERSEAL** is only suitable for use on unpainted brick, stone or render. It can not be overpainted.

Coverage

3 - 5m² per litre depending on porosity of substrate.

Storage Conditions

Store in cool, dry conditions between 5 and 30°C.

Shelf Life

12 months in original, unopened containers.

Disposal of Containers

Do not leave empty containers where residue could be harmful to children, animals or the environment. Replace lids and remove any containers to a central disposal point in accordance with local regulations.

Health & Safety

- ◆ Contains white spirit. Harmful if swallowed. May cause lung damage. If swallowed do not induce vomiting. Seek medical advice immediately and show the container label.
- ◆ Flammable. Keep away from sources of ignition. No smoking. In case of fire use foam / dry powder CO₂, NEVER USE WATER.
- ◆ Avoid release into the environment.
- ◆ Avoid contact with skin and eyes. In case of contact to eyes irrigate thoroughly for 15 minutes with clean running water.
- ◆ Do not breathe vapours.
- ◆ Keep out of reach of children.
- ◆ Wear suitable protective clothing, gloves and eye and face protection.
- ◆ Refer to relevant safety data sheet for full details.

Specification Summary

Flammability	Flammable
Chemical Composition	Polyoxysterate in white spirit
Appearance	Colourless liquid
Coverage	3-5m ² per litre dependant on substrate

Container Sizes

Code:	BDH050	BDH051
Size:	5L	25L
Barcode:	5060021364579	5060021367617

The data presented in this leaflet are in accordance with the present state of our knowledge, but do not absolve the user from carefully checking all supplies immediately on receipt. We reserve the right to alter product constants within the scope of technical progress or new developments. The recommendations made in this leaflet should be checked by preliminary trials because of conditions during processing over which we have no control, especially where other companies raw materials are also being used. The recommendations do not absolve the user from the obligation of investigating the possibility of infringement of third parties rights and, if necessary clarifying the position. Recommendations for use do not constitute a warranty, either express or implied, of the fitness or suitability of the products for a particular purpose.



Certificate Number: 6152
ISO 9001
ISO 14001



BOND IT
Unit G16 River Bank Way, Lowfields Business Park,
Elland, West Yorkshire HX5 9DN.
Telephone: +44 (0)1422 315300 Fax +44 (0)1422 315310
Email: sales@bond-it.co.uk Website: www.bond-it.co.uk



V2 29/11/12