

SAFETY DATA SHEET

according to 1907/2006/EC, Article 31

Page 1/4

XTREME CONSTRUCTION ADH

Revision 0

Revision date 2012-05-23

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product name	XTREME CONSTRUCTION ADH
Product code	BDXCA/12

1.3. Details of the supplier of the safety data sheet

Company	SEAL IT SERVICES LTD
Address	T/A BOND IT Unit G16 Riverbank Way, Lowfields Business Park, Elland, West Yorkshire HX5 9DN
Web	www.bond-it.co.uk
Telephone	01422 315300
Fax	01422 315310
Email	sales@bond-it.co.uk

1.4. Emergency telephone number


Emergency telephone number	01422 315300 8.30AM - 5.30PM Mon-Fri
----------------------------	---

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

2.1.1. Classification - 1999/45/EC	F+; R12 R52/53-67 Symbols: F+: Extremely flammable.
------------------------------------	--

2.2. Label elements

Symbols	F+: Extremely flammable. 
---------	---

SECTION 3: Composition/information on ingredients

3.2. Mixtures

67/548/EEC / 1999/45/EC

Chemical Name	Index No.	CAS No.	EC No.	REACH Registration Number	Conc. (%w/w)	Classification
D.S.P 60/95		64742-49-0			10 - 20%	F; R11 Xn; R65 Xi; R38 N; R51/53 R67
Butanone (Butan-2-one (methyl ethyl ketone))	606-002-00-3	78-93-3	201-159-0		1 - 10%	F; R11 Xi; R36 R66 R67
Xylene (Xylene, o-,m-,p-or mixed isomers)	601-022-00-9	1330-20-7	215-535-7		1 - 10%	R10 Xn; R20/21 Xi; R38

XTREME CONSTRUCTION ADH

Revision 0

Revision date 2012-05-23

3.2. Mixtures

SECTION 4: First aid measures

SECTION 5: Firefighting measures

SECTION 6: Accidental release measures

SECTION 7: Handling and storage

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

8.1.1. Exposure Limit Values

Butanone (Butan-2-one (methyl ethyl ketone))	WEL 8-hr limit ppm: 200	WEL 8-hr limit mg/m3: 600
	WEL 15 min limit ppm: 300	WEL 15 min limit mg/m3: 899
Xylene (Xylene, o-,m-,p-or mixed isomers)	WEL 8-hr limit ppm: 50	WEL 8-hr limit mg/m3: 220
	WEL 15 min limit ppm: 100	WEL 15 min limit mg/m3: 441

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

State	Liquid
Colour	Brown
Odour	Characteristic
pH	No data available
Melting point	No data available
Freezing Point	No data available
Boiling point	35 °C
Flash point	-4 °C
Evaporation rate	No data available
Flammability limits	No data available
Vapour Flammability	No data available
Vapour pressure	No data available
Vapour density	No data available
Relative density	1.26 (Water = 1 @ 20 °C)
Fat Solubility	No data available
Partition coefficient	No data available
Autoignition temperature	No data available
Viscosity	7 x 10 ⁻⁶ m ² /s @ 40 °C (ISO 3104/3105)
Explosive	No data available
Oxidising	No data available
Solubility	No data available

XTREME CONSTRUCTION ADH

Revision 0

Revision date 2012-05-23

9.2. Other information

Conductivity	No data available
Surface tension	No data available
Gas group	No data available

SECTION 10: Stability and reactivity

SECTION 11: Toxicological information

11.1.4. Toxicological Information

	No data available
--	-------------------

SECTION 12: Ecological information

12.1. Toxicity

	No data available
--	-------------------

SECTION 13: Disposal considerations

SECTION 14: Transport information

Hazard pictograms

	
--	---

14.1. UN number

	UN1133
--	--------

14.2. UN proper shipping name

	ADHESIVES
--	-----------

14.3. Transport hazard class(es)

ADR/RID	3
Subsidiary risk	-
IMDG	3
Subsidiary risk	-
IATA	3
Subsidiary risk	-

14.4. Packing group

Packing group	II
---------------	----

14.5. Environmental hazards

Environmental hazards	No
Marine pollutant	No

ADR/RID

Hazard ID	33
Tunnel Category	(D/E)

IMDG

EmS Code	F-E S-D
----------	---------

IATA

XTREME CONSTRUCTION ADH

Revision 0

Revision date 2012-05-23

IATA	
Packing Instruction (Cargo)	364
Maximum quantity	60L
Packing Instruction (Passenger)	353
Maximum quantity	5L

SECTION 15: Regulatory information**SECTION 16: Other information**

Other information	
Text of risk phrases in Section 3	R10 - Flammable R11 - Highly flammable. R20/21 - Harmful by inhalation and in contact with skin. R36 - Irritating to eyes. R38 - Irritating to skin. R51/53 - Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment. R65 - Harmful: may cause lung damage if swallowed. R66 - Repeated exposure may cause skin dryness or cracking. R67 - Vapours may cause drowsiness and dizziness.