

# SAFETY DATA SHEET

according to 1907/2006/EC, Article 31

Page 1/6


## FELT ADHESIVE CLP

Revision 2  
Revision date 2015-05-19

### SECTION 1: Identification of the substance/mixture and of the company/undertaking

<b>1.1. Product identifier</b>	
<b>Product name</b>	FELT ADHESIVE CLP
<b>1.3. Details of the supplier of the safety data sheet</b>	
<b>Company</b>	SEAL IT SERVICES LTD
<b>Address</b>	T/A BOND IT Unit G16 Riverbank Way, Lowfields Business Park, Elland, West Yorkshire HX5 9DN
<b>Web</b>	www.bond-it.co.uk
<b>Telephone</b>	01422 315300
<b>Fax</b>	01422 315310
<b>Email</b>	sales@bond-it.co.uk
<b>1.4. Emergency telephone number</b>	
<b>Emergency telephone number</b>	01422 315300 8.30AM - 5.30PM Mon-Fri

### SECTION 2: Hazards identification

<b>2.1. Classification of the substance or mixture</b>	
<b>2.1.1. Classification - 67/548/EEC</b>	Xn; R65 N; R51/53 R10-66-67 Symbols: Xn: Harmful. N: Dangerous for the environment.
<b>Main hazards</b>	Flammable. Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment. Harmful: may cause lung damage if swallowed. Repeated exposure may cause skin dryness or cracking. Vapours may cause drowsiness and dizziness.
<b>2.1.2. Classification - EC 1272/2008</b>	EUH066; Flam. Liq. 3: H226; Asp. Tox. 1: H304; STOT SE 3: H336; Aquatic Chronic 2: H411;
<b>2.2. Label elements</b>	
<b>Hazard pictograms</b>	
<b>Signal Word</b>	Danger
<b>Hazard Statement</b>	EUH066 - Repeated exposure may cause skin dryness or cracking. Flam. Liq. 3: H226 - Flammable liquid and vapour. Asp. Tox. 1: H304 - May be fatal if swallowed and enters airways. STOT SE 3: H336 - May cause drowsiness or dizziness. Aquatic Chronic 2: H411 - Toxic to aquatic life with long lasting effects.
<b>Precautionary Statement: Prevention</b>	P210 - Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. P233 - Keep container tightly closed.

## FELT ADHESIVE CLP

Revision 2

Revision date 2015-05-19

## 2.2. Label elements

Precautionary Statement: Response	P240 - Ground/bond container and receiving equipment. P241 - Use explosion-proof electrical/ventilating/lighting// equipment. P242 - Use only non-sparking tools. P243 - Take precautionary measures against static discharge. P261 - Avoid breathing dust/fume/gas/mist/vapours/spray. P271 - Use only outdoors or in a well-ventilated area. P273 - Avoid release to the environment. P280 - Wear protective gloves/protective clothing/eye protection/face protection.
	P301+P310 - IF SWALLOWED: IF SWALLOWED: Immediately call a POISON CENTER/doctor/ . P303+P361+P353 - IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower. P304+P340 - IF INHALED: Remove person to fresh air and keep comfortable for breathing. P312 - Call a POISON CENTER/doctor/ /if you feel unwell. P331 - Do NOT induce vomiting. P370+P378 - In case of fire: Use to extinguish. P391 - Collect spillage.
Precautionary Statement: Storage	P403+P233 - Store in a well-ventilated place. Keep container tightly closed. P403+P235 - Store in a well-ventilated place. Keep cool. P405 - Store locked up.
Precautionary Statement: Disposal	P501 - Dispose of contents/container to meet National Legislation and Environmental Regulations

## SECTION 3: Composition/information on ingredients

## 3.1. Substances

## 67/548/EEC / 1999/45/EC

Chemical Name	Index No.	CAS No.	EC No.	REACH Registration Number	Conc. (%w/w)	Classification	M-factor.
White Spirit			919-446-0		30 - 40%	Xn; R65 N; R51/53 R10-66-67	

## EC 1272/2008

Chemical Name	Index No.	CAS No.	EC No.	REACH Registration Number	Conc. (%w/w)	Classification	M-factor.
White Spirit			919-446-0		30 - 40%	EUH066; Flam. Liq. 3: H226; Asp. Tox. 1: H304; STOT SE 3: H336; Aquatic Chronic 2: H411;	

## SECTION 4: First aid measures

## 4.1. Description of first aid measures

Inhalation	Move the exposed person to fresh air.
Eye contact	Rinse immediately with plenty of water for 15 minutes holding the eyelids open.
Skin contact	Wash off immediately with plenty of soap and water. Remove contaminated clothing.
Ingestion	DO NOT INDUCE VOMITING.

## 4.2. Most important symptoms and effects, both acute and delayed

Inhalation	Inhalation may cause coughing, tightness of the chest and irritation of the respiratory system.
Eye contact	May cause irritation to eyes.
Skin contact	May cause irritation to skin.
Ingestion	Ingestion may cause nausea and vomiting.

## 4.3. Indication of any immediate medical attention and special treatment needed

Inhalation	Seek medical attention.
Eye contact	Seek medical attention if irritation or symptoms persist.
Skin contact	Seek medical attention if irritation or symptoms persist.
Ingestion	Seek medical attention if irritation or symptoms persist.

# FELT ADHESIVE CLP

Revision 2

Revision date 2015-05-19

## General information

In case of accident or if you feel unwell, seek medical advice immediately (show the label where possible).

## SECTION 5: Firefighting measures

### 5.1. Extinguishing media

Carbon oxides. Alcohol resistant foam.

### 5.2. Special hazards arising from the substance or mixture

. Burning produces irritating, toxic and obnoxious fumes.

### 5.3. Advice for firefighters

Wear suitable respiratory equipment when necessary.

## SECTION 6: Accidental release measures

### 6.1. Personal precautions, protective equipment and emergency procedures

Ensure adequate ventilation of the working area. Evacuate personnel to a safe area. Eliminate all sources of ignition. Wear suitable protective equipment.

### 6.2. Environmental precautions

Do not allow product to enter drains. Prevent further spillage if safe.

### 6.3. Methods and material for containment and cleaning up

Absorb with inert, absorbent material. Transfer to suitable, labelled containers for disposal. Clean spillage area thoroughly with plenty of water.

## SECTION 7: Handling and storage

### 7.1. Precautions for safe handling

Avoid contact with eyes and skin. Ensure adequate ventilation of the working area. Use explosion proof equipment. Keep away from sources of ignition - No smoking.

### 7.2. Conditions for safe storage, including any incompatibilities

Keep in a cool, dry, well ventilated area. Keep containers tightly closed. Store in correctly labelled containers.

## SECTION 8: Exposure controls/personal protection

### 8.2. Exposure controls

#### 8.2.1. Appropriate engineering controls

Ensure adequate ventilation of the working area.

#### 8.2.2. Individual protection measures

Wear chemical protective clothing.

#### Eye / face protection

Approved safety goggles.

#### Skin protection - Handprotection

Chemical resistant gloves (PVC).

#### Respiratory protection

Wear suitable respiratory equipment when necessary.

## SECTION 9: Physical and chemical properties

### 9.1. Information on basic physical and chemical properties

## FELT ADHESIVE CLP

Revision 2

Revision date 2015-05-19

## 9.1. Information on basic physical and chemical properties

Appearance	Liquid
Colour	Black
Odour	Aromatic
pH	No data available
Melting point	No data available
Initial boiling point	No data available
Flash point	38 °C
Evaporation rate	No data available
Freezing Point	No data available
Flammability (solid, gas)	No data available
Autoignition temperature	No data available
Vapour pressure	No data available
Relative density	0.96 (H <sub>2</sub> O = 1 @ 20 °C)
Partition coefficient	No data available
Viscosity	No data available
Vapour density	No data available
Fat Solubility	No data available
Explosive properties	No data available
Oxidising properties	No data available
Solubility	No data available

## 9.2. Other information

Conductivity	No data available
Gas group	No data available
Surface tension	No data available

## SECTION 10: Stability and reactivity

## 10.2. Chemical stability

	Stable under normal conditions.
--	---------------------------------

## 10.3. Possibility of hazardous reactions

	Oxidising agents.
--	-------------------

## 10.4. Conditions to avoid

	Heat, sparks and open flames.
--	-------------------------------

## SECTION 11: Toxicological information

## 11.1.4. Toxicological Information

	No data available
--	-------------------

## SECTION 12: Ecological information

## 12.1. Toxicity

	No data available
	Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

## 12.3. Bioaccumulative potential

## Partition coefficient

	FELT ADHESIVE CLP No data available
--	-------------------------------------

## SECTION 13: Disposal considerations

## General information

## FELT ADHESIVE CLP

Revision 2

Revision date 2015-05-19

## General information

Dispose of in compliance with all local and national regulations.

## SECTION 14: Transport information

## Hazard pictograms



## 14.1. UN number

UN1263

## 14.2. UN proper shipping name

PAINT RELATED MATERIAL

## 14.3. Transport hazard class(es)

ADR/RID 3

Subsidiary risk -

IMDG 3

Subsidiary risk -

IATA 3

Subsidiary risk -

## 14.4. Packing group

Packing group III

## 14.5. Environmental hazards

Environmental hazards Yes

Marine pollutant Yes

## ADR/RID

Hazard ID 30

Tunnel Category (D/E)

## IMDG

EmS Code F-E S-E

## IATA

Packing Instruction (Cargo) 366

Maximum quantity 220 L

Packing Instruction (Passenger) 355

Maximum quantity 60 L

## SECTION 15: Regulatory information

## 15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

Regulations	COMMISSION REGULATION (EU) No 453/2010 of 20 May 2010 amending Regulation (EC) No 1907/2006 of the European Parliament and of the Council on the Registration, Authorisation and Restriction of Chemicals (REACH), establishing a European Chemicals Agency, amending Directive 1999/45/EC and repealing Council Regulation (EEC) No 793/93 and Commission Regulation (EC) No 1488/94 as well as Council Directive 76/769/EEC and Commission Directives 91/155/EEC, 93/67/EEC, 93/105/EEC and 2000/21/EC.
-------------	---

## SECTION 16: Other information

## Other information

Revision	This document differs from the previous version in the following areas:.
----------	--

## FELT ADHESIVE CLP

Revision 2

Revision date 2015-05-19

Other information	
Text of risk phrases in Section 3	2 - Precautionary Statement: Disposal.
	R10 - Flammable R51/53 - Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment. R65 - Harmful: may cause lung damage if swallowed. R66 - Repeated exposure may cause skin dryness or cracking. R67 - Vapours may cause drowsiness and dizziness.
Text of Hazard Statements in Section 3	EUH066 - Repeated exposure may cause skin dryness or cracking. Flam. Liq. 3: H226 - Flammable liquid and vapour. Asp. Tox. 1: H304 - May be fatal if swallowed and enters airways. STOT SE 3: H336 - May cause drowsiness or dizziness. Aquatic Chronic 2: H411 - Toxic to aquatic life with long lasting effects.
Further information	
	The information supplied in this Safety Data Sheet is designed only as guidance for the safe use, storage and handling of the product. This information is correct to the best of our knowledge and belief at the date of publication however no guarantee is made to its accuracy. This information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any other process.