

# SAFETY DATA SHEET

according to 1907/2006/EC, Article 31

Page 1/6

## ALUMINIUM PAINT CLP

Revision 2  
Revision date 2015-05-19

### SECTION 1: Identification of the substance/mixture and of the company/undertaking

#### 1.1. Product identifier

<b>Product name</b>	ALUMINIUM PAINT CLP
---------------------	---------------------

#### 1.3. Details of the supplier of the safety data sheet

<b>Company</b>	SEAL IT SERVICES LTD
<b>Address</b>	T/A BOND IT Unit G16 Riverbank Way, Lowfields Business Park, Elland, West Yorkshire HX5 9DN
<b>Web</b>	www.bond-it.co.uk
<b>Telephone</b>	01422 315300
<b>Fax</b>	01422 315310
<b>Email</b>	sales@bond-it.co.uk

#### 1.4. Emergency telephone number


<b>Emergency telephone number</b>	01422 315300 8.30AM - 5.30PM Mon-Fri
-----------------------------------	---

### SECTION 2: Hazards identification

#### 2.1. Classification of the substance or mixture

<b>2.1.1. Classification - 67/548/EEC</b>	Xn; R65 N; R51/53 R10-66-67 Symbols: Xn: Harmful. N: Dangerous for the environment.
<b>Main hazards</b>	Flammable. Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment. Harmful: may cause lung damage if swallowed. Repeated exposure may cause skin dryness or cracking. Vapours may cause drowsiness and dizziness.
<b>2.1.2. Classification - EC 1272/2008</b>	EUH066; Flam. Liq. 3: H226; Asp. Tox. 1: H304; STOT SE 3: H336; Aquatic Chronic 2: H411;

#### 2.2. Label elements

<b>Hazard pictograms</b>	
<b>Signal Word</b>	Danger
<b>Hazard Statement</b>	EUH066 - Repeated exposure may cause skin dryness or cracking. Flam. Liq. 3: H226 - Flammable liquid and vapour. Asp. Tox. 1: H304 - May be fatal if swallowed and enters airways. STOT SE 3: H336 - May cause drowsiness or dizziness. Aquatic Chronic 2: H411 - Toxic to aquatic life with long lasting effects.
<b>Precautionary Statement: Prevention</b>	P210 - Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. P233 - Keep container tightly closed.

## ALUMINIUM PAINT CLP

Revision 2

Revision date 2015-05-19

## 2.2. Label elements

Precautionary Statement: Response	P240 - Ground/bond container and receiving equipment. P241 - Use explosion-proof electrical/ventilating/lighting// equipment. P242 - Use only non-sparking tools. P243 - Take precautionary measures against static discharge. P261 - Avoid breathing dust/fume/gas/mist/vapours/spray. P271 - Use only outdoors or in a well-ventilated area. P273 - Avoid release to the environment. P280 - Wear protective gloves/protective clothing/eye protection/face protection.
	P301+P310 - IF SWALLOWED: IF SWALLOWED: Immediately call a POISON CENTER/doctor/ . P303+P361+P353 - IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower. P304+P340 - IF INHALED: Remove person to fresh air and keep comfortable for breathing. P312 - Call a POISON CENTER/doctor/ /if you feel unwell. P331 - Do NOT induce vomiting. P370+P378 - In case of fire: Use to extinguish. P391 - Collect spillage.
	P403+P233 - Store in a well-ventilated place. Keep container tightly closed. P403+P235 - Store in a well-ventilated place. Keep cool. P405 - Store locked up.
Precautionary Statement: Storage	
Precautionary Statement: Disposal	P501 - Dispose of contents/container to meet National Legislation and Environmental Regulations

## SECTION 3: Composition/information on ingredients

## 3.1. Substances

67/548/EEC / 1999/45/EC

Chemical Name	Index No.	CAS No.	EC No.	REACH Registration Number	Conc. (%w/w)	Classification	M-factor.
White Spirit			919-446-0			Xn; R65 N; R51/53 R10-66-67	

EC 1272/2008

Chemical Name	Index No.	CAS No.	EC No.	REACH Registration Number	Conc. (%w/w)	Classification	M-factor.
White Spirit			919-446-0			EUH066; Flam. Liq. 3: H226; Asp. Tox. 1: H304; STOT SE 3: H336; Aquatic Chronic 2: H411;	

## SECTION 4: First aid measures

## 4.1. Description of first aid measures

Inhalation	Move the exposed person to fresh air.
Eye contact	Rinse immediately with plenty of water for 15 minutes holding the eyelids open.
Skin contact	Wash off immediately with plenty of soap and water. Remove contaminated clothing.
Ingestion	DO NOT INDUCE VOMITING.

## 4.2. Most important symptoms and effects, both acute and delayed

Inhalation	Harmful by inhalation. Inhalation may cause nausea and vomiting. May cause dizziness and headache.
Eye contact	May cause irritation to eyes.
Skin contact	May cause dermatitis. May cause irritation to skin.
Ingestion	Harmful if swallowed. Ingestion is irritating to the respiratory tract and may cause damage to the central nervous system. Ingestion may cause nausea and vomiting.

## 4.3. Indication of any immediate medical attention and special treatment needed

Inhalation	Seek medical attention.
Eye contact	Seek medical attention if irritation or symptoms persist.
Skin contact	Seek medical attention if irritation or symptoms persist.

## ALUMINIUM PAINT CLP

Revision 2

Revision date 2015-05-19

**4.3. Indication of any immediate medical attention and special treatment needed**

Ingestion	If swallowed, seek medical advice immediately and show this container or label.
-----------	---

**SECTION 5: Firefighting measures****5.1. Extinguishing media**

	Use as appropriate: Carbon dioxide (CO <sub>2</sub> ), Dry chemical, Foam.
--	--

**5.2. Special hazards arising from the substance or mixture**

	Burning produces irritating, toxic and obnoxious fumes.
--	---

**5.3. Advice for firefighters**

	Self-contained breathing apparatus. Wear protective clothing.
--	---

**SECTION 6: Accidental release measures****6.1. Personal precautions, protective equipment and emergency procedures**

	Ensure adequate ventilation of the working area. Wear suitable protective equipment.
--	--

**6.2. Environmental precautions**

	Do not allow product to enter drains. Prevent further spillage if safe.
--	---

**6.3. Methods and material for containment and cleaning up**

	Absorb with inert, absorbent material. Transfer to suitable, labelled containers for disposal. Clean spillage area thoroughly with plenty of water.
--	---

**SECTION 7: Handling and storage****7.1. Precautions for safe handling**

	Avoid contact with eyes and skin. Ensure adequate ventilation of the working area. Adopt best Manual Handling considerations when handling, carrying and dispensing.
--	--

**7.2. Conditions for safe storage, including any incompatibilities**

	Keep in a cool, dry, well ventilated area. Keep containers tightly closed.
--	--

**SECTION 8: Exposure controls/personal protection****8.2. Exposure controls**

8.2.1. Appropriate engineering controls	Ensure adequate ventilation of the working area.
---	--

8.2.2. Individual protection measures	Wear chemical protective clothing.
---------------------------------------	------------------------------------

Eye / face protection	Approved safety goggles.
-----------------------	--------------------------

Skin protection - Handprotection	Chemical resistant gloves (PVC).
----------------------------------	----------------------------------

Respiratory protection	Self-contained breathing apparatus. Wear protective clothing.
------------------------	---

**SECTION 9: Physical and chemical properties****9.1. Information on basic physical and chemical properties**

## ALUMINIUM PAINT CLP

Revision 2

Revision date 2015-05-19

## 9.1. Information on basic physical and chemical properties

Appearance	Liquid
Colour	Black
Odour	Aromatic
pH	No data available
Melting point	No data available
Initial boiling point	No data available
Flash point	38 °C
Evaporation rate	No data available
Freezing Point	No data available
Flammability (solid, gas)	No data available
Autoignition temperature	No data available
Vapour pressure	No data available
Relative density	No data available
Partition coefficient	No data available
Viscosity	No data available
Vapour density	No data available
Fat Solubility	No data available
Explosive properties	No data available
Solubility	Insoluble in water

## 9.2. Other information

Conductivity	No data available
Gas group	No data available
Surface tension	No data available

## SECTION 10: Stability and reactivity

## 10.2. Chemical stability

	Stable under normal conditions.
--	---------------------------------

## SECTION 11: Toxicological information

## 11.1.4. Toxicological Information

	No data available
--	-------------------

## SECTION 12: Ecological information

## 12.1. Toxicity

	No data available
	Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

## 12.3. Bioaccumulative potential

## Partition coefficient

	ALUMINIUM PAINT CLP No data available
--	---------------------------------------

## SECTION 13: Disposal considerations

## General information

	Dispose of in compliance with all local and national regulations.
--	---

## SECTION 14: Transport information

## Hazard pictograms

## ALUMINIUM PAINT CLP

Revision 2

Revision date 2015-05-19

Hazard pictograms	
14.1. UN number	UN1263
14.2. UN proper shipping name	PAINT RELATED MATERIAL
14.3. Transport hazard class(es)	
ADR/RID	3
Subsidiary risk	-
IMDG	3
Subsidiary risk	-
IATA	3
Subsidiary risk	-
14.4. Packing group	
Packing group	III
14.5. Environmental hazards	
Environmental hazards	Yes
Marine pollutant	Yes
ADR/RID	
Hazard ID	30
Tunnel Category	(D/E)
IMDG	
EmS Code	F-E S-E
IATA	
Packing Instruction (Cargo)	366
Maximum quantity	220 L
Packing Instruction (Passenger)	355
Maximum quantity	60 L
<b>SECTION 15: Regulatory information</b>	
15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture	
Regulations	COMMISSION REGULATION (EU) No 453/2010 of 20 May 2010 amending Regulation (EC) No 1907/2006 of the European Parliament and of the Council on the Registration, Authorisation and Restriction of Chemicals (REACH), establishing a European Chemicals Agency, amending Directive 1999/45/EC and repealing Council Regulation (EEC) No 793/93 and Commission Regulation (EC) No 1488/94 as well as Council Directive 76/769/EEC and Commission Directives 91/155/EEC, 93/67/EEC, 93/105/EEC and 2000/21/EC.
<b>SECTION 16: Other information</b>	
Other information	
Revision	This document differs from the previous version in the following areas: 2 - Precautionary Statement: Disposal.
Text of risk phrases in Section 3	R10 - Flammable R51/53 - Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

## ALUMINIUM PAINT CLP

Revision 2

Revision date 2015-05-19

## Other information

Text of Hazard Statements in Section 3	R65 - Harmful: may cause lung damage if swallowed. R66 - Repeated exposure may cause skin dryness or cracking. R67 - Vapours may cause drowsiness and dizziness.
	EUH066 - Repeated exposure may cause skin dryness or cracking. Flam. Liq. 3: H226 - Flammable liquid and vapour. Asp. Tox. 1: H304 - May be fatal if swallowed and enters airways. STOT SE 3: H336 - May cause drowsiness or dizziness. Aquatic Chronic 2: H411 - Toxic to aquatic life with long lasting effects.

## Further information

	The information supplied in this Safety Data Sheet is designed only as guidance for the safe use, storage and handling of the product. This information is correct to the best of our knowledge and belief at the date of publication however no guarantee is made to its accuracy. This information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any other process.
--	--