

SAFETY DATA SHEET

according to 1907/2006/EC, Article 31

Page 1/6

BDLM LINEMARKER PAINT CLP

Revision 2
Revision date 2015-05-20

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product name	BDLM LINEMARKER PAINT CLP
---------------------	---------------------------

1.3. Details of the supplier of the safety data sheet

Company	SEAL IT SERVICES LTD
Address	T/A BOND IT Unit G16 Riverbank Way, Lowfields Business Park, Elland, West Yorkshire HX5 9DN
Web	www.bond-it.co.uk
Telephone	01422 315300
Fax	01422 315310
Email	sales@bond-it.co.uk

1.4. Emergency telephone number


Emergency telephone number	01422 315300 8.30AM - 5.30PM Mon-Fri
-----------------------------------	---

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

2.1.1. Classification - 67/548/EEC	F+; R12 Xi; R36 R52/53-66-67 Symbols: F+: Extremely flammable. Xi: Irritant.
Main hazards	Extremely flammable. Irritating to eyes. Harmful to aquatic organisms, may cause long-term adverse effects in the aquatic environment. Repeated exposure may cause skin dryness or cracking. Vapours may cause drowsiness and dizziness.
2.1.2. Classification - EC 1272/2008	EUH066; Aerosols 1: H222; Flam. Liq. 2: H225; Eye Irrit. 2: H319; STOT SE 3: H336; Aquatic Chronic 3: H412;

2.2. Label elements

Hazard pictograms	
Signal Word	Danger
Hazard Statement	EUH066 - Repeated exposure may cause skin dryness or cracking. Aerosols 1: H222 - Extremely flammable aerosol. Flam. Liq. 2: H225 - Highly flammable liquid and vapour. Eye Irrit. 2: H319 - Causes serious eye irritation. STOT SE 3: H336 - May cause drowsiness or dizziness. Aquatic Chronic 3: H412 - Harmful to aquatic life with long lasting effects.
Precautionary Statement: Prevention	P210 - Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

BDLM LINEMARKER PAINT CLP

Revision 2

Revision date 2015-05-20

2.2. Label elements

Precautionary Statement: Response	P211 - Do not spray on an open flame or other ignition source. P233 - Keep container tightly closed. P240 - Ground/bond container and receiving equipment. P241 - Use explosion-proof electrical/ventilating/lighting// equipment. P242 - Use only non-sparking tools. P243 - Take precautionary measures against static discharge. P251 - Do not pierce or burn, even after use. P261 - Avoid breathing dust/fume/gas/mist/vapours/spray. P264 - Wash thoroughly after handling. P271 - Use only outdoors or in a well-ventilated area. P273 - Avoid release to the environment. P280 - Wear protective gloves/protective clothing/eye protection/face protection.
	P303+P361+P353 - IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower. P304+P340 - IF INHALED: Remove person to fresh air and keep comfortable for breathing. P305+P351+P338 - IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. P312 - Call a POISON CENTER/doctor/ /if you feel unwell. P337+P313 - If eye irritation persists: Get medical advice/attention. P370+P378 - In case of fire: Use to extinguish.
Precautionary Statement: Storage	P403+P233 - Store in a well-ventilated place. Keep container tightly closed. P403+P235 - Store in a well-ventilated place. Keep cool. P405 - Store locked up. P410+P412 - Protect from sunlight. Do no expose to temperatures exceeding 50°C/ 122°F.
Precautionary Statement: Disposal	P501 - Dispose of contents/container to meet National Legislation and Environmental Regulations

SECTION 3: Composition/information on ingredients

3.1. Substances

67/548/EEC / 1999/45/EC

Chemical Name	Index No.	CAS No.	EC No.	REACH Registration Number	Conc. (%w/w)	Classification	M-factor.
Butane	601-004-00-0	106-97-8	203-448-7			F+, R12	

EC 1272/2008

Chemical Name	Index No.	CAS No.	EC No.	REACH Registration Number	Conc. (%w/w)	Classification	M-factor.
Butane	601-004-00-0	106-97-8	203-448-7			Flam. Gas 1: H220;	
Propane	601-003-00-5	74-98-6	200-827-9			Flam. Gas 1: H220;	
Acetone	606-001-00-8	67-64-1	200-662-2			Flam. Liq. 2: H225; Eye Irrit. 2: H319; STOT SE 3: H336; EUH066; Flam. Liq. 3: H226;	
Mixed Aromatic Hydrocarbons		64742-95-6				Asp. Tox. 1: H304; STOT SE 3: H335; STOT SE 3: H336; Aquatic Chronic 2: H411;	
n-Butyl acetate (Butyl acetate)	607-025-00-1	123-86-4	204-658-1			Flam. Liq. 3: H226; STOT SE 3: H336;	
Isobutane	601-004-00-0	75-28-5	200-857-2			Flam. Gas 1: H220;	

SECTION 4: First aid measures

4.1. Description of first aid measures

Inhalation	Move the exposed person to fresh air.
Eye contact	Rinse immediately with plenty of water for 15 minutes holding the eyelids open.
Skin contact	Wash off immediately with plenty of soap and water. Remove contaminated clothing.
Ingestion	DO NOT INDUCE VOMITING.

BDLM LINEMARKER PAINT CLP

Revision 2

Revision date 2015-05-20

4.2. Most important symptoms and effects, both acute and delayed

Inhalation	Inhalation may cause coughing, tightness of the chest and irritation of the respiratory system.
Eye contact	May cause irritation to eyes.
Skin contact	May cause irritation to skin.
Ingestion	Ingestion may cause nausea and vomiting.

4.3. Indication of any immediate medical attention and special treatment needed

Inhalation	Seek medical attention.
Eye contact	Seek medical attention if irritation or symptoms persist.
Skin contact	Seek medical attention if irritation or symptoms persist.
Ingestion	Seek medical attention if irritation or symptoms persist.

General information

	In case of accident or if you feel unwell, seek medical advice immediately (show the label where possible).
--	---

SECTION 5: Firefighting measures

5.1. Extinguishing media

	Carbon oxides. Alcohol resistant foam.
--	--

5.2. Special hazards arising from the substance or mixture

	Vapour may travel considerable distance to source of ignition and flash back.
--	---

5.3. Advice for firefighters

	Wear suitable respiratory equipment when necessary.
--	---

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

	Ensure adequate ventilation of the working area. Evacuate personnel to a safe area. Eliminate all sources of ignition. Wear suitable protective equipment.
--	--

6.2. Environmental precautions

	Do not allow product to enter drains. Prevent further spillage if safe.
--	---

6.3. Methods and material for containment and cleaning up

	Absorb with inert, absorbent material. Transfer to suitable, labelled containers for disposal. Clean spillage area thoroughly with plenty of water.
--	---

SECTION 7: Handling and storage

7.1. Precautions for safe handling

	Avoid contact with eyes and skin. Ensure adequate ventilation of the working area. Use explosion proof equipment. Keep away from sources of ignition - No smoking.
--	--

7.2. Conditions for safe storage, including any incompatibilities

	Keep in a cool, dry, well ventilated area. Keep containers tightly closed. Store in correctly labelled containers.
--	--

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

8.1.1. Exposure Limit Values

Butane	WEL 8-hr limit ppm:	600	WEL 8-hr limit mg/m3:	1450
	WEL 15 min limit ppm:	750	WEL 15 min limit mg/m3:	1810
	WEL 8-hr limit mg/m3 total	-	WEL 15 min limit mg/m3 total	-
	inhalable dust:		inhalable dust:	
	WEL 8-hr limit mg/m3 total	-	WEL 15 min limit mg/m3 total	-
	respirable dust:		respirable dust:	

BDLM LINEMARKER PAINT CLP

Revision 2

Revision date 2015-05-20

8.2. Exposure controls

8.2.1. Appropriate engineering controls	Ensure adequate ventilation of the working area.
8.2.2. Individual protection measures	Wear chemical protective clothing.
Eye / face protection	Approved safety goggles.
Skin protection - Handprotection	Chemical resistant gloves (PVC).
Respiratory protection	Wear suitable respiratory equipment when necessary.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Appearance	Aerosol
Colour	White
Odour	Characteristic
Flash point	< -40 °C
Explosive properties	No data available

SECTION 10: Stability and reactivity

10.2. Chemical stability

	Stable under normal conditions.
--	---------------------------------

10.3. Possibility of hazardous reactions

	Oxidising agents.
--	-------------------

10.4. Conditions to avoid

	Heat, sparks and open flames.
--	-------------------------------

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Acute toxicity	No data is available on this product.
Skin corrosion/irritation	No data is available on this product.
Serious eye damage/irritation	No data is available on this product.
Respiratory or skin sensitisation	No data is available on this product.
Germ cell mutagenicity	No data is available on this product.
Carcinogenicity	No data is available on this product.
Reproductive toxicity	No data is available on this product.

SECTION 12: Ecological information

12.2. Persistence and degradability

	No data is available on this product.
--	---------------------------------------

12.3. Bioaccumulative potential

	No data is available on this product.
--	---------------------------------------

12.4. Mobility in soil

	No data is available on this product.
--	---------------------------------------

12.5. Results of PBT and vPvB assessment

	No data is available on this product.
--	---------------------------------------

SECTION 13: Disposal considerations

General information

	Dispose of in compliance with all local and national regulations.
--	---

BDLM LINEMARKER PAINT CLP

Revision 2

Revision date 2015-05-20

SECTION 14: Transport information

Hazard pictograms



14.1. UN number

UN1950

14.2. UN proper shipping name

AEROSOLS

14.3. Transport hazard class(es)

ADR/RID	2
Subsidiary risk	see SP63
IMDG	2
Subsidiary risk	see SP63
IATA	2
Subsidiary risk	see SP63

14.4. Packing group

Packing group	-
---------------	---

14.5. Environmental hazards

Environmental hazards	No
Marine pollutant	No

ADR/RID

Hazard ID	-
Tunnel Category	(D)

IMDG

EmS Code	F-D S-U
----------	---------

IATA

Packing Instruction (Cargo)	203
Maximum quantity	150 kg
Packing Instruction (Passenger)	203
Maximum quantity	75 kg

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

Regulations	COMMISSION REGULATION (EU) No 453/2010 of 20 May 2010 amending Regulation (EC) No 1907/2006 of the European Parliament and of the Council on the Registration, Authorisation and Restriction of Chemicals (REACH), establishing a European Chemicals Agency, amending Directive 1999/45/EC and repealing Council Regulation (EEC) No 793/93 and Commission Regulation (EC) No 1488/94 as well as Council Directive 76/769/EEC and Commission Directives 91/155/EEC, 93/67/EEC, 93/105/EEC and 2000/21/EC.
-------------	---

SECTION 16: Other information

Other information

Revision	This document differs from the previous version in the following areas: 2 - Precautionary Statement: Disposal.
Text of risk phrases in Section 3	R12 - Extremely flammable.

BDLM LINEMARKER PAINT CLP

Revision 2

Revision date 2015-05-20

Other information**Text of Hazard Statements in Section 3**

Flam. Gas 1: H220 - Extremely flammable gas.
EUH066 - Repeated exposure may cause skin dryness or cracking.
Flam. Liq. 2: H225 - Highly flammable liquid and vapour.
Eye Irrit. 2: H319 - Causes serious eye irritation.
STOT SE 3: H336 - May cause drowsiness or dizziness.
Flam. Liq. 3: H226 - Flammable liquid and vapour.
Asp. Tox. 1: H304 - May be fatal if swallowed and enters airways.
STOT SE 3: H335 - May cause respiratory irritation.
Aquatic Chronic 2: H411 - Toxic to aquatic life with long lasting effects.

Further information

The information supplied in this Safety Data Sheet is designed only as guidance for the safe use, storage and handling of the product. This information is correct to the best of our knowledge and belief at the date of publication however no guarantee is made to its accuracy. This information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any other process.