

SAFETY DATA SHEET

according to 1907/2006/EC, Article 31

Page 1/6

PC800 PIPESEAL CLP



Revision 1

Revision date 2015-05-20

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier	
Product name	PC800 PIPESEAL CLP
1.3. Details of the supplier of the safety data sheet	
Company	SEAL IT SERVICES LTD
Address	T/A BOND IT Unit G16 Riverbank Way, Lowfields Business Park, Elland, West Yorkshire HX5 9DN
Web	www.bond-it.co.uk
Telephone	01422 315300
Fax	01422 315310
Email	sales@bond-it.co.uk
1.4. Emergency telephone number	
Emergency telephone number	01422 315300 8.30AM - 5.30PM Mon-Fri

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture	
2.1.1. Classification - 67/548/EEC	F+; R12 Xi; R36 R66-67 Symbols: F+: Extremely flammable. Xi: Irritant.
Main hazards	Extremely flammable. Irritating to eyes. Repeated exposure may cause skin dryness or cracking. Vapours may cause drowsiness and dizziness.
2.1.2. Classification - EC 1272/2008	Flam. Liq. 2: H225; Eye Irrit. 2: H319; STOT SE 3: H336;
2.2. Label elements	
Hazard pictograms	 
Signal Word	Danger
Hazard Statement	EUH066 - Repeated exposure may cause skin dryness or cracking. Flam. Liq. 2: H225 - Highly flammable liquid and vapour. Eye Irrit. 2: H319 - Causes serious eye irritation. STOT SE 3: H336 - May cause drowsiness or dizziness.
Precautionary Statement: Prevention	P210 - Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. P233 - Keep container tightly closed. P240 - Ground/bond container and receiving equipment. P241 - Use explosion-proof electrical/ventilating/lighting// equipment.

PC800 PIPESEAL CLP

Revision 1

Revision date 2015-05-20

2.2. Label elements

Precautionary Statement: Response	P242 - Use only non-sparking tools. P243 - Take precautionary measures against static discharge. P261 - Avoid breathing dust/fume/gas/mist/vapours/spray. P264 - Wash thoroughly after handling. P271 - Use only outdoors or in a well-ventilated area. P280 - Wear protective gloves/protective clothing/eye protection/face protection.
	P303+P361+P353 - IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower. P304+P340 - IF INHALED: Remove person to fresh air and keep comfortable for breathing. P305+P351+P338 - IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. P312 - Call a POISON CENTER/doctor/ /if you feel unwell. P337+P313 - If eye irritation persists: Get medical advice/attention. P370+P378 - In case of fire: Use to extinguish.
Precautionary Statement: Storage	P403+P233 - Store in a well-ventilated place. Keep container tightly closed. P403+P235 - Store in a well-ventilated place. Keep cool. P405 - Store locked up.
Precautionary Statement: Disposal	P501 - Dispose of contents/container to meet National Legislation and Environmental Regulations

SECTION 3: Composition/information on ingredients

3.1. Substances

67/548/EEC / 1999/45/EC

Chemical Name	Index No.	CAS No.	EC No.	REACH Registration Number	Conc. (%w/w)	Classification	M-factor.
Butanone (Butan-2-one (methyl ethyl ketone))	606-002-00-3	78-93-3	201-159-0			F; R11 Xi; R36 R66 R67	
Cyclohexanone	606-010-00-7	108-94-1	203-631-1			R10 Xn; R20	

EC 1272/2008

Chemical Name	Index No.	CAS No.	EC No.	REACH Registration Number	Conc. (%w/w)	Classification	M-factor.
Butanone (Butan-2-one (methyl ethyl ketone))	606-002-00-3	78-93-3	201-159-0			Flam. Liq. 2: H225; Eye Irrit. 2: H319; STOT SE 3: H336;	
Cyclohexanone	606-010-00-7	108-94-1	203-631-1			Flam. Liq. 3: H226; Acute Tox. 4: H332;	

SECTION 4: First aid measures

4.1. Description of first aid measures

Inhalation	Move the exposed person to fresh air.
Eye contact	Rinse immediately with plenty of water for 15 minutes holding the eyelids open.
Skin contact	Wash off immediately with plenty of soap and water. Remove contaminated clothing.
Ingestion	DO NOT INDUCE VOMITING.

4.2. Most important symptoms and effects, both acute and delayed

Inhalation	Inhalation may cause coughing, tightness of the chest and irritation of the respiratory system. Irritating to respiratory system.
Eye contact	Irritating to eyes.
Skin contact	Irritating to skin.
Ingestion	Ingestion may cause nausea and vomiting.

4.3. Indication of any immediate medical attention and special treatment needed

Inhalation	Seek medical attention.
Eye contact	Seek medical attention if irritation or symptoms persist.
Skin contact	Seek medical attention if irritation or symptoms persist.
Ingestion	Seek medical attention if irritation or symptoms persist.

PC800 PIPESEAL CLP

Revision 1

Revision date 2015-05-20

SECTION 5: Firefighting measures**5.1. Extinguishing media**

Carbon oxides.

5.2. Special hazards arising from the substance or mixture

Burning produces irritating, toxic and obnoxious fumes. Vapour may travel considerable distance to source of ignition and flash back.

5.3. Advice for firefighters

Self-contained breathing apparatus. Wear protective clothing.

SECTION 6: Accidental release measures**6.1. Personal precautions, protective equipment and emergency procedures**

Ensure adequate ventilation of the working area. Wear suitable protective equipment. Eliminate all sources of ignition. Evacuate personnel to a safe area.

6.2. Environmental precautions

Do not allow product to enter drains. Prevent further spillage if safe.

6.3. Methods and material for containment and cleaning up

Absorb with inert, absorbent material. Sweep up. Transfer to suitable, labelled containers for disposal. Clean spillage area thoroughly with plenty of water.

SECTION 7: Handling and storage**7.1. Precautions for safe handling**

Avoid contact with eyes and skin. Ensure adequate ventilation of the working area. Use explosion proof equipment. Keep away from sources of ignition - No smoking.

7.2. Conditions for safe storage, including any incompatibilities

Keep in a cool, dry, well ventilated area. Keep containers tightly closed. Store in correctly labelled containers.

SECTION 8: Exposure controls/personal protection**8.1. Control parameters****8.1.1. Exposure Limit Values**

Butanone (Butan-2-one (methyl ethyl ketone))	WEL 8-hr limit ppm: 200	WEL 8-hr limit mg/m3: 600
	WEL 15 min limit ppm: 300	WEL 15 min limit mg/m3: 899
	WEL 8-hr limit mg/m3 total - inhalable dust:	WEL 15 min limit mg/m3 total - inhalable dust:
	WEL 8-hr limit mg/m3 total - respirable dust:	WEL 15 min limit mg/m3 total - respirable dust:
Cyclohexanone	WEL 8-hr limit ppm: 10	WEL 8-hr limit mg/m3: 10
	WEL 15 min limit ppm: 20	WEL 15 min limit mg/m3: 82
	WEL 8-hr limit mg/m3 total - inhalable dust:	WEL 15 min limit mg/m3 total - inhalable dust:
	WEL 8-hr limit mg/m3 total - respirable dust:	WEL 15 min limit mg/m3 total - respirable dust:

8.2. Exposure controls**8.2.1. Appropriate engineering controls**

Ensure adequate ventilation of the working area.

8.2.2. Individual protection measures

Wear chemical protective clothing.

Eye / face protection

Approved safety goggles.

Skin protection - Handprotection

Chemical resistant gloves (PVC).

PC800 PIPESEAL CLP

Revision 1

Revision date 2015-05-20

8.2. Exposure controls

Respiratory protection	Wear suitable respiratory equipment when necessary.
------------------------	---

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Appearance	Gel
Colour	Colourless
Odour	Characteristic
Odour threshold	No data available
Melting point	No data available
Freezing Point	No data available
Initial boiling point	No data available
Flash point	-4 °C
Flammability (solid, gas)	No data available
Autoignition temperature	No data available
Explosive properties	No data available
Oxidising properties	No data available
Vapour pressure	No data available
Relative density	0.92 (H ₂ O = 1 @ 20 °C)
Viscosity	No data available
Vapour density	No data available
Evaporation rate	No data available
Solubility	Immiscible in water

9.2. Other information

Conductivity	No data available
Gas group	No data available
Surface tension	No data available
VOC (Volatile organic compounds)	No data available
Benzene Content	No data available
Lead content	No data available

SECTION 10: Stability and reactivity

10.2. Chemical stability

	Stable under normal conditions.
--	---------------------------------

10.3. Possibility of hazardous reactions

	Oxidising agents.
--	-------------------

10.4. Conditions to avoid

	Heat, sparks and open flames.
--	-------------------------------

SECTION 11: Toxicological information

11.1.4. Toxicological Information

	No data available
--	-------------------

SECTION 12: Ecological information

12.1. Toxicity

	No data available
--	-------------------

SECTION 13: Disposal considerations

General information

	Dispose of in compliance with all local and national regulations.
--	---

PC800 PIPESEAL CLP

Revision 1

Revision date 2015-05-20

SECTION 14: Transport information

Hazard pictograms



14.1. UN number

UN1133

14.2. UN proper shipping name

ADHESIVES

14.3. Transport hazard class(es)

ADR/RID 3

Subsidiary risk -

IMDG 3

Subsidiary risk -

IATA 3

Subsidiary risk -

14.4. Packing group

Packing group III

14.5. Environmental hazards

Environmental hazards No

Marine pollutant No

ADR/RID

Hazard ID 33

Tunnel Category (D/E)

IMDG

EmS Code F-E S-D

IATA

Packing Instruction (Cargo) 366

Maximum quantity 220L

Packing Instruction 355

(Passenger)

Maximum quantity 60L

Further information

The product is not classified as dangerous for carriage.

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

Regulations	COMMISSION REGULATION (EU) No 453/2010 of 20 May 2010 amending Regulation (EC) No 1907/2006 of the European Parliament and of the Council on the Registration, Authorisation and Restriction of Chemicals (REACH), establishing a European Chemicals Agency, amending Directive 1999/45/EC and repealing Council Regulation (EEC) No 793/93 and Commission Regulation (EC) No 1488/94 as well as Council Directive 76/769/EEC and Commission Directives 91/155/EEC, 93/67/EEC, 93/105/EEC and 2000/21/EC.
--------------------	---

SECTION 16: Other information

Other information

Revision	This document differs from the previous version in the following areas:.
-----------------	--

PC800 PIPESEAL CLP

Revision 1

Revision date 2015-05-20

Other information	
Text of risk phrases in Section 3	2 - Precautionary Statement: Disposal.
	R10 - Flammable R11 - Highly flammable. R20 - Harmful by inhalation. R36 - Irritating to eyes. R66 - Repeated exposure may cause skin dryness or cracking. R67 - Vapours may cause drowsiness and dizziness.
Text of Hazard Statements in Section 3	EUH066 - Repeated exposure may cause skin dryness or cracking. Flam. Liq. 2: H225 - Highly flammable liquid and vapour. Eye Irrit. 2: H319 - Causes serious eye irritation. STOT SE 3: H336 - May cause drowsiness or dizziness. Flam. Liq. 3: H226 - Flammable liquid and vapour. Acute Tox. 4: H332 - Harmful if inhaled.
Further information	
	The information supplied in this Safety Data Sheet is designed only as guidance for the safe use, storage and handling of the product. This information is correct to the best of our knowledge and belief at the date of publication however no guarantee is made to its accuracy. This information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any other process.