

## DECLARATION OF PERFORMANCE

### DOP - WP70

- |  |   |
|--|---|
| 1 Identification Code:                                 | Bond It WP70 Oxime Silicone   |
| 2. Batch Identification:                               | By batch number – see print on packaging  |
| 3. Intended uses:                                      | <b>F EXT-INT</b> Façade Sealant for Interior Use<br><b>G</b> Glazing sealant <b>S1</b> Sanitary sealant                   |
| 4. Manufacturer:                                       | Seal It Services t/a Bond It<br>Unit G16 River Bank Way<br>Lowfields Business Park<br>Elland<br>West Yorkshire<br>HX5 9DN |
| 5. Authorised Representative:                          | Not applicable  |
| 6. System of assessment and Verification of constancy: | System 3  |
| 7. Notified Body:                                      | 0757  |
| 8. European Technical Assessment:                      | Not Applicable  |
| 9. Declared performance:                               |   |

ESSENTIAL CHARACTERISTIC	DECLARED PERFORMANCE	HARMONISED STANDARD
Reaction to Fire	Class E	
Release of Chemicals	None	See MSDS
Water Tightness and Air Tightness as determined by:		EN 15651-1:2012
Resistance to Flow	≤3mm	Conditioning method B Tested on Mortar M1 with primer
Loss of Volume	≤30%	
Tensile properties after water immersion at 23°C	≥25%	
Tensile properties at maintained extension	Pass	EN15651-2:2012
Adhesion/cohesion at variable temperatures	Pass	Conditioning method B Glass without primer
Adhesion/cohesion at maintained extension after water immersion	Pass	
Microbiological Growth	1	EN15651-2:2012
Durability	Pass	Conditioning method B Aluminium without primer

10. The performance of the product identified in points 1 and 2 is in conformity with the declared performance in point 9.

Signed for and on behalf of the manufacturer by:



Phil Radford  
Technical Manager  
Elland  
15 Oct 2015

